



# Wall mounted unit

FTXJ-MW/S



BLUEEVOLUTION



Silver allergen removal and air purifying filter



2 area intelligent eye



Whisper quiet



Online controller via app



Multi model application

## Design at its best, delivering superior efficiency and comfort

- › Seasonal efficiency values up to A+++
- › Silver allergen removal and air purifying filter: captures allergens such as pollen and dust mites. The filter suppresses pollen and mites for 99% or more.
- › Online controller (optional): control your

indoor from any location with an app, via your local network or internet and keep an overview on your energy consumption

- › Whisper quiet in operation: the operating of the unit can hardly be heard. The sound pressure level goes down to 19dBA!

# FTXJ-MW/S + RXJ-M



Indoor unit		FTXJ	20MW/S	25MW/S	35MW/S	50MW/S
Casing	Colour		White/Silver			
Dimensions	Unit	HeightxWidthxDepth	mm			
			303x998x212			
Sound power level	Cooling	dB(A)	54		59	60
	Heating	dB(A)	56		59	60
Sound pressure level	Cooling	High/Low/Silent operation	dB(A)		45/26/20	46/35/32
	Heating	High/Low/Silent operation	dB(A)		45/29/20	47/35/32
Control systems	Infrared remote control		ARC466A9			
Refrigerant	Type	R-32				
	GWP	675				

EER/COP according to Eurovent 2012, for use outside EU only | Nominal efficiency: cooling at 35°/27° nominal load, heating at 7°/20° nominal load


Efficiency data		FTXJ + RXJ	20MW + 20M	25MW + 25M	35MW + 35M	50MW + 50M	
Cooling capacity	Nom.	kW	2.3	2.4	3.5	4.8	
Heating capacity	Nom.	kW	2.50	3.20	4	5.80	
Power input	Cooling	Nom. kW	0.50	0.51	0.86	1.43	
	Heating	Nom. kW	0.50	0.70	0.99	1.59	
Seasonal efficiency (according to EN14825)	Cooling	Energy label	A+++		A++		
		Pdesign	kW	2.30	2.40	3.50	4.80
		SEER		8.73	8.64	7.19	7.02
	Heating (Average climate)	Annual energy consumption	kWh	92	97	170	239
		Energy label		A++		A+	
Nominal efficiency	EER	Pdesign	kW	2.10	2.70	3.00	4.60
		SCOP/A		4.61	4.60		4.28
	COP	Annual energy consumption	kWh	638	822	913	1,505
		EER		4.64	4.73	4.09	3.35
	Energy label	Cooling/Heating		5.00	4.57	4.04	3.65
Annual energy consumption	kWh	248	254	428	716		
Energy label	Cooling/Heating		A/A				

EER/COP according to Eurovent 2012, for use outside EU only | Nominal efficiency: cooling at 35°/27° nominal load, heating at 7°/20° nominal load

Outdoor unit		RXJ	20M	25M	35M	50M
Dimensions	Unit	HeightxWidthxDepth	mm			735x825x300
Sound power level	Cooling	dB(A)	61		63	
	Heating	dB(A)	62		63	
Sound pressure level	Cooling	High/Silent operation	dB(A)		48/45	
	Heating	High/Silent operation	dB(A)		48/45	
Operation range	Cooling	Ambient	Min.-Max.	°CDB		
	Heating	Ambient	Min.-Max.	°CWB		
Refrigerant	Type/Charge/GWP	R-32/0.72/0.5/675				R-32/1.30/0.9/675
Power supply	Phase/Frequency/Voltage	Hz/V				1~/50/220-240

Contains fluorinated greenhouse gases

**Daikin Europe N.V.** Naamloze Vennootschap · Zandvoordestraat 300 · 8400 Oostende · Belgium · www.daikin.eu · BE 0412 120 336 · RPR Oostende (Responsible Editor)



ECPEN16-041

04/16



Daikin Europe N.V. participates in the Eurovent Certification programme for Liquid Chilling Packages (LCP), Air handling units (AHU), Fan coil units (FCU) and variable refrigerant flow systems (VRF) Check ongoing validity of certificate online: www.eurovent-certification.com or using: www.certiflash.com



The present leaflet is drawn up by way of information only and does not constitute an offer binding upon Daikin Europe N.V. Daikin Europe N.V. has compiled the content of this leaflet to the best of its knowledge. No express or implied warranty is given for the completeness, accuracy, reliability or fitness for particular purpose of its content and the products and services presented therein. Specifications are subject to change without prior notice. Daikin Europe N.V. explicitly rejects any liability for any direct or indirect damage, in the broadest sense, arising from or related to the use and/or interpretation of this leaflet. All content is copyrighted by Daikin Europe N.V.